



- ① BITUMINOUS CONCRETE CLASS 2 (SURFACE COURSE)
- ① BITUMINOUS CONCRETE CLASS 1 (BINDER COURSE)
- ① PROCESSED AGGREGATE BASE
- ① GRAVEL SUBBASE

- ② 4" TOPSOIL, GRADE, SEED AND MULCH
- ② REMOVE BOULDERS AND LEDGE ROCK TO A DEPTH OF 12 INCHES BELOW SUBGRADE, AND REPLACE WITH GRAVEL SUBBASE MATERIAL

- NOTES:**
1. PAVEMENT WIDTH, MATERIAL DEPTHS AND OTHER CONSTRUCTION DETAILS AS SHOWN ON PLATES 1-6 FOR THE APPROPRIATE ROAD CLASSIFICATION.
 2. REQUIRED DIMENSIONS MAY BE MODIFIED BASED ON SITE SPECIFIC DESIGN AND WITH APPROVAL OF TOWN ENGINEER.
 3. IN FILL SITUATIONS, LOCATE SWALE AT BASE OF FILL SLOPE IN EXISTING GROUND. FILL SLOPE TO BE DESIGNED TO RESIST EROSION.
 4. 50" MINIMUM; ADJUST WIDTH OF RIGHT OF WAY AS REQUIRED TO ENCOMPASS ENTIRE SWALE SYSTEM.
 5. 4" TOPSOIL PLACED OVER 8" SUITABLE ON-SITE SANDS AND GRAVELS IN SHOULDER AREAS. IF NO SUITABLE MATERIAL PRESENT REPLACE WITH BANK RUN GRAVEL.

STANDARD DETAIL DRAWING
TYPICAL ROAD SECTION
 ROADWAY UTILIZING SURFACE DRAINAGE SYSTEM

HEBRON
 PUBLIC IMPROVEMENT
 SPECIFICATIONS

REVISIONS:

SCALE: NONE

DATE: OCTOBER, 2001 PLATE 6